





SPECIFICATION



Model Name		PT043-WSK
Sub-models		-
Display	Size	4.3" diagonal
	Max. Resolution	480*272
	Type	TFT LCD with LED Backlight
	Max. Colors	16-bit
	Backlight Life (hr)	20,000
	Display Contrast	500
	Luminance (cd/m2)	280
Touch Panel		N/A
CPU		RISC ARM9 32Bit
Battery Backed RAM		128KB (Optional: 1MB)
Working Memory		32MB
Built-in Storage Memory		8MB
Real-Time Clock (RTC)		YES
Communication Interface	Micro SD Slot	N/A
	USB Client	YES (USB 2.0)
	USB Host	YES (USB 1.1)
	Serial (Com1)	RS232/422/485
	Serial (Com2)	RS422 / 485
	Serial (Com3)	RS232 only (optional:RS485 only)
	Serial (Com4)	N/A
	Ethernet	N/A
Front Function Keys		23-keys
Audio out (optional)		N/A
Video in (optional)		N/A
Front USB Host Port		N/A
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	10W
Environment	Operating Temperature	-10°C~+60°C
	Relative Humidity	10%~90%
	Shock (operation)	10 ~ 55Hz (X,Y,Z direction, 1G, 30 Mins shock testing)
	EMI	FCC Part 15 Class A
	CE	EN61000-6-2, EN61000-6-4
	UL Certification	N/A
	Ingress Protection	IP66
	Cooling	Natural Cooling
Dimension WxHxD (mm)		172.0 x 102.0 x 30
Cutout Dimension WxH (mm)		160.5 x 89.5
Net Weight (kg)		0.33



**Panel Cut Out Dimensions:
160.5 x 89.5 mm**