



SPECIFICATION



Model Name		PV035-TST / TNT
Sub-models		-
Display	Size	3.5" diagonal
	Max. Resolution	320*240
	Type	TFT LCD with LED Backlight
	Max. Colors	256 colors
	Backlight Life (hr)	20,000
	Luminance (cd/m2)	300
Operation		4-wire Analog Resistive Type
CPU		RISC ARM9 32Bit
Backup SRAM		128KB (optional: 1024KB)
Working Memory		4MB
Built-in Storage Memory		1MB / 2MB
Real-Time Clock (RTC)		YES
Communication Interface	Micro SD Slot	N/A
	USB Client	N/A
	USB Host	N/A
	Serial (Com1)	RS232/422/485
	Serial (Com2)	Terminal 5pin : RS422/RS485
	Serial (Com3)	N/A
	Serial (Com4)	N/A
Ethernet		N/A / YES
Front Function Keys		N/A
Audio out (optional)		N/A
Video in (optional)		N/A
Front USB Host Port		N/A
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	10W
Environment	Operating Temperature	0°C~50°C
	Relative Humidity	10%~90%
	Shock (operation)	10 ~ 55Hz (X,Y,Z direction, 1G, 30 Mins shock testing)
	EMI	FCC Part 15 Class A
	CE	EN61000-6-2, EN61000-6-4
	UL Certification	N/A
	Ingress Protection	IP65
Cooling		Natural Cooling
Dimension WxHxD (mm)		130 x 106.2 x 39
Cutout Dimension WxH (mm)		119 x 93
Net Weight (kg)		0.26



Panel Cut Out Dimensions: 119 x 93 mm