

FCC DoC TEST REPORT

for

LCD Touch Control Panel

MODEL: PA2100; eA2100; GA2100; xPA2100; AT2100; MMPA2100; FA2100; MA2100;
NA2100; XA2100; AU2100; LA2100; AHM2100A; ASA-2100; VA82100; KL2100;
xPL2100; FL2100; ML2100; GL2100; NL2100; XL2100; THM2100A; PK2100; eK2100;
GK2100; PK2100; xPK2100; KK2100; MMPK2100; FK2100; MK2100; NK2100; XK2100;
KU2100; LK2100; KHM2100A; ASK-2100; VK82100; KHM2100B; TK2100; iPK2100;
iPK2100B; IW410;IW410B; GK2100; NK2100; VK2100; xPK2100; LUI2100; FK2100;
MA2100;TA2100; iPA2100; VA2100

Test Report Number:

T170426D21-F

Issued to:

Cermate Technologies Inc.

7F-1, No.168, Lien Cheng Rd., Chung-Ho District,
New Taipei City, Taiwan 235

Issued by:

Compliance Certification Services Inc.

Xindian Lab.

No.163-1, Jhongsheng Rd., Xindian Dist.,
New Taipei City, 23151 Taiwan.

TEL: 886-2-22170894

FAX: 886-2-22171029

Issued Date: May 11, 2017



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NIST or any government agencies. The test results in the report only apply to the tested sample.

Revision History

Rev.		Issue Date		Revisions	Effect Page	Revised By
00		May 11, 2017		Initial Issue	ALL	Wendy Wang

TABLE OF CONTENTS

1	TEST RESULT CERTIFICATION	4
2	EUT DESCRIPTION.....	5
3	TEST METHODOLOGY.....	6
3.1.	DECISION OF FINAL TEST MODE.....	6
3.2.	EUT SYSTEM OPERATION	6
4	SETUP OF EQUIPMENT UNDER TEST	7
4.1.	DESCRIPTION OF SUPPORT UNITS	7
4.2.	CONFIGURATION OF SYSTEM UNDER TEST	7
5	FACILITIES AND ACCREDITATIONS	8
5.1.	FACILITIES	8
5.2.	ACCREDITATIONS.....	8
5.3.	MEASUREMENT UNCERTAINTY.....	8
6	CONDUCTED EMISSION MEASUREMENT	9
6.1.	LIMITS OF CONDUCTED EMISSION MEASUREMENT	9
6.2.	TEST INSTRUMENTS	9
6.3.	TEST PROCEDURES.....	10
6.4.	TEST SETUP	11
6.5.	DATA SAMPLE	11
6.6.	TEST RESULTS.....	12
7	RADIATED EMISSION MEASUREMENT	16
7.1.	LIMITS OF RADIATED EMISSION MEASUREMENT.....	16
7.2.	TEST INSTRUMENTS	17
7.3.	TEST PROCEDURES.....	18
7.4.	TEST SETUP	19
7.5.	DATA SAMPLE	20
7.6.	TEST RESULTS.....	21
8	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	27
	APPENDIX 1 - PHOTOGRAPHS OF EUT	A1-1

1 TEST RESULT CERTIFICATION

Product: LCD Touch Control Panel

Model: PA2100; eA2100; GA2100; xPA2100; AT2100; MMPA2100; FA2100; MA2100; NA2100; XA2100; AU2100; LA2100; AHM2100A; ASA-2100; VA82100; KL2100; xPL2100; FL2100; ML2100; GL2100; NL2100; XL2100; THM2100A; PK2100; eK2100; GK2100; PK2100; xPK2100; KK2100; MMPK2100; FK2100; MK2100; NK2100; XK2100; KU2100; LK2100; KHM2100A; ASK-2100; VK82100; KHM2100B; TK2100; iPK2100; iPK2100B; IW410; IW410B; GK2100; NK2100; VK2100; xPK2100; LUI2100; FK2100; MA2100; TA2100; iPA2100; VA2100

Brand: Cermate

Applicant: Cermate Technologies Inc.
7F-1, No.168, Lien Cheng Rd., Chung-Ho District,
New Taipei City, Taiwan 235

Manufacturer: Cermate Technologies Inc.
7F-1, No.168, Lien Cheng Rd., Chung-Ho District,
New Taipei City, Taiwan 235

Tested: April 21, 2017 ~ May 10, 2017


EMISSION			
Standard	Item	Result	Remarks
FCC 47 CFR Part 15 Subpart B, ICES-003 Issue 6-2016 ANSI C63.4-2014	Conducted (Power Port)	PASS	Meet Class A limit
	Radiated	PASS	Meet Class A limit

- Note:**
1. The statements of test result on the above are decided by the request of test standard only; the measurement uncertainties are not factored into this compliance determination.
 2. The information of measurement uncertainty is available upon the customer's request.

Deviation from Applicable Standard
None


The above equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:



Sam Hu
Assistant Manager

Reviewed by:



Eva Fan
Supervisor of report document dept.

2 EUT DESCRIPTION

Product	LCD Touch Control Panel
Brand Name	Cermate
Model	PA2100; eA2100; GA2100; xPA2100; AT2100; MMPA2100; FA2100; MA2100; NA2100; XA2100; AU2100; LA2100; AHM2100A; ASA-2100; VA82100; KL2100; xPL2100; FL2100; ML2100; GL2100; NL2100; XL2100; THM2100A; PK2100; eK2100; GK2100; PK2100; xPK2100; KK2100; MMPK2100; FK2100; MK2100; NK2100; XK2100; KU2100; LK2100; KHM2100A; ASK-2100; VK82100; KHM2100B; TK2100; iPK2100; iPK2100B; IW410;IW410B; GK2100; NK2100; VK2100; xPK2100; LUI2100; FK2100; MA2100;TA2100; iPA2100; VA2100
Applicant	Cermate Technologies Inc.
Housing material	Plastic
Identify Number	T170426D21
Received Date	April 26, 2017
EUT Power Rating	24VDC from DC Power Supply

Model Differences

Model Name	Difference	Tested (Checked)
PA2100	Original	<input checked="" type="checkbox"/>
eA2100; GA2100; xPA2100; AT2100; MMPA2100; FA2100; MA2100; NA2100; XA2100; AU2100; LA2100; AHM2100A; ASA-2100; VA82100; KL2100; xPL2100; FL2100; ML2100; GL2100; NL2100; XL2100; THM2100A; PK2100; eK2100; GK2100; PK2100; xPK2100; KK2100; MMPK2100; FK2100; MK2100; NK2100; XK2100; KU2100; LK2100; KHM2100A; ASK-2100; VK82100; KHM2100B; TK2100; iPK2100; iPK2100B; IW410;IW410B; GK2100; NK2100; VK2100; xPK2100; LUI2100; FK2100; MA2100;TA2100; iPA2100; VA2100	For marketing purpose only.	<input type="checkbox"/>

I/O PORT

I/O PORT TYPES	Q'TY	TESTED WITH
1. COM1 / COM2 / COM3 Port	1	1
2. USB Port	2	2
3. SD Slot	1	N/A

Note: Client consigns only one model sample to test (Model Number: PA2100).

3 TEST METHODOLOGY

3.1. DECISION OF FINAL TEST MODE

The EUT was tested together with the below additional components, and a configuration, which produced the worst emission levels, was selected and recorded in this report.

The test configuration/ modes are as the following:

Conduction Modes:

1	DC Power Mode
2	AC Power Mode

Radiation Mode:

1	Normal Mode
	Normal Mode / 1-18GHz

Worst:

Conduction: Mode 1

Radiation: Mode 1

3.2. EUT SYSTEM OPERATION

1. All peripherals connect EUT to test.

Note: Test program is self-repeating throughout the test.

4 SETUP OF EQUIPMENT UNDER TEST

4.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

EUT Devices:

No.	Equipment	Model No.	Brand Name
1	Motherboard	070H04-16	Cermate
2	CPU (300MHz)	NUC972DF62Y	nuvoTon
3	Memory (64M Bytes (built-in CPU)	N/A	N/A
4	Storage (NAND Flash 128M bytes on board)	N/A	N/A


Peripherals Devices:

No.	Equipment	Model No.	Serial No.	FCC ID / BSMI ID	Brand Name	Data Cable	Power Cord
1	Power Supply	S-50-24	N/A	N/A	MEAN WELL	Unshielded, 0.3m	Unshielded, 1.8m
2	USB Flash Drive	SDCZ52-016G	N/A	D33724	SanDisk	N/A	N/A
3	LCD Touch Control Panel	PK2070	N/A	N/A	Cermate	COM1 / COM2 / COM3: Shielded, 2.0m	Unshielded, 1.8m
4	USB Cable	N/A	N/A	N/A	N/A	Unshielded, 1.8m	N/A

Note:

- 1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.2. CONFIGURATION OF SYSTEM UNDER TEST



5 FACILITIES AND ACCREDITATIONS

5.1. FACILITIES

All measurement facilities used to collect the measurement data are located at CCSrf Taiwan Xindian Lab. at No.163-1, Jhongsheng Rd., Xindian Dist., New Taipei City, 23151 Taiwan.

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR 16-1-1, CISPR 16-1-2, CISPR 16-1-3, CISPR 16-1-4 and CISPR 16-1-5.

5.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

Taiwan	TAF
USA	A2LA

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada	Industry Canada
Japan	VCCI
Taiwan	BSMI
USA	FCC

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsrf.com>

5.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Uncertainty
Conducted emissions	0.15MHz ~ 30MHz	± 1.07
Radiated emissions	30MHz ~ 1000MHz	± 4.82
	1000MHz ~ 18000MHz	± 4.17
	18000MHz ~ 26000MHz	± 2.18
	26000MHz ~ 40000MHz	± 2.64

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Consistent with industry standard (e.g. CISPR 22: 2005, clause 11, Measurement Uncertainty) determining compliance with the limits shall be based on the results of the compliance measurement. Consequently the measured emissions being less than the maximum allowed emission result in this being a compliant test or passing test.

The acceptable measurement uncertainty value without requiring revision of the compliance statement is based on conducted and radiated emissions being less than U_{CISPR} which is 3.6dB and 5.2dB respectively. CCS values (called U_{Lab} in CISPR 16-4-2) is less than U_{CISPR} as shown in the table above. Therefore, MU need not be considered for compliance.

6 CONDUCTED EMISSION MEASUREMENT

6.1. LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

NOTE:

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

6.2. TEST INSTRUMENTS

Conducted Emission room # A				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
BNC CABLE	EMCI	CFD300-NL	BNC#A8	05/18/2017
EMI Test Receiver	R&S	ESCI	101201	08/19/2017
LISN	Schwarzbeck	NNLK 8129	8129-286	08/18/2017
LISN(EUT)	Schwarzbeck	NSLK 8127	8127527	08/18/2017
Pulse Limiter	R&S	ESH3Z2	C3010026-2	08/22/2017
Thermo-Hygro Meter	Wisewind	201A	No. 02	05/01/2018
Test S/W	EZ-EMC			

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. N.C.R = No Calibration Request.


6.3. TEST PROCEDURES (please refer to measurement standard or CCS SOP PA-031)**Procedure of Preliminary Test**

- The EUT and support equipment, if needed, were set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor standing equipment, it is placed on the ground plane, which has a 12 mm non-conductive covering to insulate the EUT from the ground plane.
- All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- The test equipment EUT installed by AC 120VAC/60Hz main power, through a Line Impedance Stabilization Network (LISN), which was supplied power source and was grounded to the ground plane.
- All support equipment power by from a second LISN.
- The test program of the EUT was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The Receiver scanned from 150kHz to 30MHz for emissions in each of the test modes.
- During the above scans, the emissions were maximized by cable manipulation.
- The test mode(s) described in Item 3.1 were scanned during the preliminary test.
- After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.
- The worst configuration of EUT and cable of the above highest emission level were recorded for reference of the final test.

Procedure of Final Test

- EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.
- The test data of the worst-case condition(s) was recorded.

6.4. TEST SETUP



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

6.5. DATA SAMPLE

Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
x.xx	42.95	0.55	43.50	73	-29.50	Q	L1


Freq. = Emission frequency in MHz
 Reading = Uncorrected Analyzer/Receiver reading
 Factor = Insertion loss of LISN + Cable Loss + Pulse Limit
 Result = Reading + Factor
 Limit = Limit stated in standard
 Margin = Reading in reference to limit
 P = Peak Reading
 Q = Quasi-peak Reading
 A = Average Reading
 L1 = Hot side
 L2 = Neutral side

Calculation Formula

Margin (dB) = Result (dBuV) – Limit (dBuV)

6.6. TEST RESULTS


Model No.	PA2100	6dB Bandwidth	9 kHz
Environmental Conditions	20°C, 61% RH	Test Mode	Mode 1 / Worst
Tested by	Alee Shen	Phase	L1
Standard	FCC CLASS A		



Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.1540	50.95	10.11	61.06	79.00	-17.94	P	L1
0.3220	44.56	10.12	54.68	79.00	-24.32	P	L1
0.4140	43.92	10.13	54.05	79.00	-24.95	P	L1
0.7900	36.64	10.14	46.78	73.00	-26.22	P	L1
2.3940	45.53	10.36	55.89	73.00	-17.11	P	L1
20.4340	23.24	11.22	34.46	73.00	-38.54	P	L1

Note: L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).


Model No.	PA2100	6dB Bandwidth	9 kHz
Environmental Conditions	20°C, 61% RH	Test Mode	Mode 1 / Worst
Tested by	Alee Shen	Phase	L2
Standard	FCC CLASS A		



Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.1580	49.91	10.06	59.97	79.00	-19.03	P	L2
0.3300	45.15	10.07	55.22	79.00	-23.78	P	L2
0.4220	47.21	10.10	57.31	79.00	-21.69	P	L2
0.5780	43.35	10.13	53.48	73.00	-19.52	P	L2
2.3900	45.53	10.28	55.81	73.00	-17.19	P	L2
21.2380	21.60	11.37	32.97	73.00	-40.03	P	L2

Note: L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).


Model No.	PA2100	6dB Bandwidth	9 kHz
Environmental Conditions	20°C, 61% RH	Test Mode	Mode 2
Tested by	Alee Shen	Phase	L1
Standard	FCC CLASS A		



Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.1500	37.58	10.11	47.69	79.00	-31.31	P	L1
0.2420	41.68	10.12	51.80	79.00	-27.20	P	L1
0.4180	39.80	10.13	49.93	79.00	-29.07	P	L1
1.6580	42.37	10.28	52.65	73.00	-20.35	P	L1
2.3700	44.74	10.36	55.10	73.00	-17.90	P	L1
20.8100	22.60	11.28	33.88	73.00	-39.12	P	L1

Note: L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

Model No.	PA2100	6dB Bandwidth	9 kHz
Environmental Conditions	20°C, 61% RH	Test Mode	Mode 2
Tested by	Alee Shen	Phase	L2
Standard	FCC CLASS A		



Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.2420	41.44	10.04	51.48	79.00	-27.52	P	L2
0.4180	39.79	10.10	49.89	79.00	-29.11	P	L2
1.1860	39.07	10.21	49.28	73.00	-23.72	P	L2
2.2340	42.18	10.26	52.44	73.00	-20.56	P	L2
2.3820	43.34	10.28	53.62	73.00	-19.38	P	L2
23.1420	30.85	11.68	42.53	73.00	-30.47	P	L2

Note: L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

7 RADIATED EMISSION MEASUREMENT

7.1. LIMITS OF RADIATED EMISSION MEASUREMENT

Below 1GHz (for digital device)

FREQUENCY (MHz)	dBuV/m (At 10m)	
	Class A	Class B
30 ~ 230	40	30
230 ~ 1000	47	37

Limit tables for non-digital device:

Class A Radiated Emission limit at 10m (for others)

Frequency (MHz)	Field Strength Limit (uV/m)Q.P.	Field Strength Limit (dBuV/m)Q.P.
30 - 88	90	39
88 - 216	150	43.5
216 – 960	210	46.4
Above 960	300	49.5

Class B Radiated Emission limit at 3m (for others)

Frequency (MHz)	Field Strength Limit (uV/m)Q.P.	Field Strength Limit (dBuV/m)Q.P.
30 - 88	100	40
88 - 216	150	43.5
216 – 960	200	46
Above 960	500	54

Above 1GHz(for all device)

Frequency (MHz)	Class A (dBuV/m) (At 10m)		Class B (dBuV/m) (At 3m)	
	Average	Peak	Average	Peak
Above 1000	49.5	69.5	54	74

NOTE: (1) The lower limit shall apply at the transition frequencies.
 (2) Emission level (dBuV/m) = 20 log Emission level (uV/m).
 (3) The measurement above 1GHz is at close-in distances 3m, and determine the limit L_2 corresponding to the close-in distance d_2 by applying the following relation: $L_2 = L_1 (d_1/d_2)$, where L_1 is the specified limit in microvolts per metre (uV/m) at the distance d_1 (10m), L_2 is the new limit for distance d_2 (3m).
 So the new Class A limit above 1GHz at 3m is as following table:

Frequency (MHz)	Class A (dBuV/m) (At 3m)	
	Average	Peak
Above 1000	60	80

According to FCC Part 15.33 (b), for an unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a radiated emission limit is specified, up to the frequency shown in the following table:

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5 th harmonic of the highest frequency or 40GHz, whichever is lower

7.2. TEST INSTRUMENTS

Open Area Test Site # H				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Bilog Antenna	Teseq	CBL 6112D	36995	07/07/2017
Cable	EMEC	CFD400NL-LW	N-Type#H11	08/22/2017
EMI Test Receiver	R&S	ESCI	101340	03/28/2018
Pre-Amplifier	HP	8447D	1937A01554	09/29/2017
Thermo-Hygro Meter	Wisewind	201A	No. 03	05/31/2017
Test S/W	EZ-EMC			
Above 1GHz Used				
Horn Antenna	ETS	3117	139062	10/12/2017
K-Type Cable x 1m (1-40GHz)	Rosnol	K1K50-UP0264- K1k50-1M	160215-1	12/11/2017
Microflex Cable x 7m (1-18GHz)	Rosnol	A1K50-EW0630- A1k50-700CM	SD-R028	12/12/2017
Pre-Amplifier	HP	8449B	3008A01266	12/08/2017
Signal Analyzer	Agilent	N9010A	MY53440125	01/12/2018
Spectrum Analyzer	Agilent	E4440A	MY46185957	01/10/2018
Thermo-Hygro Meter	Wisewind	N/A	SD-R027	10/17/2017
Test S/W	EZ-EMC			

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. N.C.R = No Calibration Request.

7.3. TEST PROCEDURES (please refer to measurement standard or CCS SOP PA-031)**Procedure of Preliminary Test**


- The equipment was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane. When the EUT is a floor standing equipment, it is placed on the ground plane which has a 12 mm non-conductive covering to insulate the EUT from the ground plane.
- Support equipment, if needed, was placed as per ANSI C63.4.
- All I/O cables were positioned to simulate typical usage as per ANSI C63.4.
- The EUT received AC 120VAC/60Hz power source from the outlet socket under the turntable. All support equipment power received from another socket under the turntable.
- The antenna was placed at 3 or 10 meter away from the EUT as stated in ANSI C63.4. The antenna connected to the Spectrum Analyzer via a cable and at times a pre-amplifier would be used.
- The Analyzer / Receiver quickly scanned from 30MHz to 40GHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- The test mode(s) described in Item 3.1 were scanned during the preliminary test:
- After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.
- The worst configuration of EUT and cable of the above highest emission level were recorded for reference of the final test.

Procedure of Final Test


- EUT and support equipment were set up on the turntable as per the configuration with highest emission level in the preliminary test.
- The Analyzer / Receiver scanned from 30MHz to 40GHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- Recording at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. Below 1GHz the Q.P. reading and above 1GHz the Peak and Average reading are presented.
- The test data of the worst-case condition(s) was recorded.

7.4. TEST SETUP

Below 1GHz



Above 1GHz



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

7.5. DATA SAMPLE

Below 1GHz

Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/Q)	Pol. (H/V)
x.xx	14.0	12.2	26.2	40	-13.8	Q	H

Above 1GHz

Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
x.xx	42.95	0.55	43.50	60	-16.50	A	H

Freq. = Emission frequency in MHz
Reading = Uncorrected Analyzer/Receiver reading
Factor = Antenna Factor + Cable Loss - Amplifier Gain
Result = Reading + Factor
Limit = Limit stated in standard
Margin = Reading in reference to limit
P = Peak Reading
Q = Quasi-peak Reading
A = Average Reading
H = Antenna Polarization: Horizontal
V = Antenna Polarization: Vertical


Calculation Formula

Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)

7.6. TEST RESULTS

Below 1GHz

Model No.	PA2100	Test Mode	Mode 1
Environmental Conditions	24°C, 66% RH	6dB Bandwidth	120 kHz
Antenna Pole	Vertical	Antenna Distance	10m
Detector Function	Quasi-peak.	Tested by	Alee Shen
Standard	FCC CLASS A W/ CISPR 22 CLASS A LIMIT		




Radiated Emission Readings									
Frequency Range Investigated				30 MHz to 1000 MHz at 10m					
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
50.5099	46.80	-12.65	34.15	40.00	-5.85	100	226	Q	V
95.9900	38.90	-10.79	28.11	40.00	-11.89	100	201	Q	V
150.0100	42.01	-9.57	32.44	40.00	-7.56	100	320	Q	V
177.5200	42.60	-10.96	31.64	40.00	-8.36	100	187	Q	V
450.0300	42.10	-2.35	39.75	47.00	-7.25	400	163	Q	V
524.0300	36.50	-0.89	35.61	47.00	-11.39	400	108	Q	V

Note: 1. 30MHz to 1000MHz test is Applicable CISPR 22 standard.

2. P= Peak Reading; Q= Quasi-peak Reading.

Model No.	PA2100	Test Mode	Mode 1
Environmental Conditions	24°C, 66% RH	6dB Bandwidth	120 kHz
Antenna Pole	Horizontal	Antenna Distance	10m
Detector Function	Quasi-peak.	Tested by	Alee Shen
Standard	FCC CLASS A W/ CISPR 22 CLASS A LIMIT		




Radiated Emission Readings									
Frequency Range Investigated					30 MHz to 1000 MHz at 10m				
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
225.0300	39.80	-9.70	30.10	40.00	-9.90	400	116	Q	H
375.1099	41.30	-4.23	37.07	47.00	-9.93	400	58	Q	H
488.0300	36.00	-1.16	34.84	47.00	-12.16	100	49	Q	H
600.0100	32.50	0.68	33.18	47.00	-13.82	100	162	Q	H
675.0600	34.00	1.25	35.25	47.00	-11.75	100	135	Q	H
787.4200	32.40	2.51	34.91	47.00	-12.09	100	201	Q	H

Note: 1. 30MHz to 1000MHz test is Applicable CISPR 22 standard.
2. P= Peak Reading; Q= Quasi-peak Reading.

Above 1GHz


Model No.	PA2100	Test Mode	Mode 1
Environmental Conditions	22°C, 59% RH	6dB Bandwidth	1 MHz
Antenna Pole	Vertical	Antenna Distance	3m
Highest frequency generated or used	300MHz	Upper frequency	18000MHz
Detector Function	Peak and average.	Tested by	Mike Xie
Standard	FCC CLASS A		



Radiated Emission Readings							
Frequency Range Investigated				Above 1GHz at 3m			
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
1821.667	52.24	-4.60	47.64	80.00	-32.36	P	V
2105.000	53.05	-2.87	50.18	80.00	-29.82	P	V
2841.667	50.57	-1.99	48.58	80.00	-31.42	P	V
3493.333	54.51	-1.22	53.29	80.00	-26.71	P	V
5788.333	46.13	1.76	47.89	80.00	-32.11	P	V
10123.333	44.32	4.57	48.89	80.00	-31.11	P	V

Note: P= Peak Reading; A= Average Reading.

Model No.	PA2100	Test Mode	Mode 1
Environmental Conditions	25°C, 68% RH	6dB Bandwidth	1 MHz
Antenna Pole	Horizontal	Antenna Distance	3m
Highest frequency generated or used	300MHz	Upper frequency	18000MHz
Detector Function	Peak and average.	Tested by	Mike Xie
Standard	FCC CLASS A		




Radiated Emission Readings							
Frequency Range Investigated				Above 1GHz at 3m			
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
1821.667	58.37	-4.60	53.77	80.00	-26.23	P	H
2133.333	51.83	-2.82	49.01	80.00	-30.99	P	H
2388.333	51.65	-2.50	49.15	80.00	-30.85	P	H
2870.000	51.26	-1.95	49.31	80.00	-30.69	P	H
3068.333	51.38	-1.72	49.66	80.00	-30.34	P	H
11993.333	46.09	6.92	53.01	80.00	-26.99	P	H

Note: P= Peak Reading; A= Average Reading.


966 Chamber Test Data

Job No.:	T170426D21	Polarization:	Vertical
Standard:	FCC CLASS A W/ CISPR 22 CLASS A LIMIT	Power Source:	110VAC /60Hz
Test item:	Radiation Test	Date:	2017/04/21
Company:	Cermate Technologies Inc.	Time:	PM 05:02:10
Model:	PA2100	Temp.(°C)/Hum.(%):	26(°C)/60%
Description:	Normal Mode	Engineer Signature:	Alee Shen



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	50.5420	61.10	-25.18	35.92	40.00	-4.08	QP	
2	51.3400	64.06	-25.18	38.88	40.00	-1.12	peak	
3	96.9300	57.37	-21.51	35.86	40.00	-4.14	peak	
4	149.3100	55.69	-18.92	36.77	40.00	-3.23	peak	
5	177.4400	52.17	-17.27	34.90	40.00	-5.10	peak	
6	450.0100	54.06	-17.04	37.02	47.00	-9.98	peak	
7	524.7000	51.84	-16.40	35.44	47.00	-11.56	peak	

Job No.:	T170426D21	Polarization:	Horizontal
Standard:	FCC CLASS A W/ CISPR 22 CLASS A LIMIT	Power Source:	110VAC /60Hz
Test item:	Radiation Test	Date:	2017/04/21
Company:	Cermate Technologies Inc.	Time:	PM 05:08:11
Model:	PA2100	Temp.(°C)/Hum.(%):	26(°C)/60%
Description:	Normal Mode	Engineer Signature:	Alee Shen



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	224.9700	54.13	-23.96	30.17	40.00	-9.83	peak	
2	375.3200	50.44	-19.01	31.43	47.00	-15.57	peak	
3	487.8400	48.03	-14.19	33.84	47.00	-13.16	peak	
4	600.3600	45.58	-13.70	31.88	47.00	-15.12	peak	
5	675.0500	48.21	-13.20	35.01	47.00	-11.99	peak	
6	787.5700	46.47	-12.46	34.01	47.00	-12.99	peak	

8 PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST

AC Power



DC Power




RADIATED EMISSION TEST

Below 1GHz



Above 1GHz



966 CHAMBER TEST

